

Stoßfeste Wendelaufhängung Shock resistant helix holders



Sicherung erforderlich gem. EN 60357
Fuse needed according to EN 60357

F=Quick acting miniature fuse 250 V
with high braking capacity

F*=Quick acting D- fuses 500 V

Glühlampenverbotsverordnung/
Ecodesign requirements:

Nachfolgemodell/follow-up model
Auslaufmodell/phased-out model



Art.-Nr.	Leistung	Lichtstrom	EEK	Abmessung	Sicherung	Box	Blister	VE
Art.-no.	Wattage	Lum. flux	EEC	Dimensions	fuse			
16942	60 W	700 lm	E	78,3 mm		X		1
24942	60 W	700 lm	E	78,3 mm			X	1
15701	80 W	1450 lm	C	78,3 mm		X		1
24050	80 W	1450 lm	C	78,3 mm			X	1
15703	100 W	2000 lm	C	78,3 mm	F2,0 A	X		1
24052	100 W	2000 lm	C	78,3 mm	F2,0 A		X	1
15705	150 W	3000 lm	C	78,3 mm	F2,0 A	X		1
24054	150 W	3000 lm	C	78,3 mm	F2,0 A		X	1
15707	190 W	3800 lm	C	78,3 mm	F2,0 A	X		1
24056	190 W	3800 lm	C	78,3 mm	F2,0 A		X	1
15702	80 W	1450 lm	C	117,6 mm	F2,0 A	X		1
24051	80 W	1450 lm	C	117,6 mm	F2,0 A		X	1
15704	100 W	2000 lm	C	117,6 mm	F2,0 A	X		1
24053	100 W	2000 lm	C	117,6 mm	F2,0 A		X	1
15706	150 W	3000 lm	C	117,6 mm	F2,0 A	X		1
24055	150 W	3000 lm	C	117,6 mm	F2,0 A		X	1
15708	190 W	3800 lm	C	117,6 mm	F2,0 A	X		1
15710	240 W	5000 lm	C	117,6 mm	F2,0 A	X		1
24059	240 W	5000 lm	C	117,6 mm	F2,0 A		X	1
15712	400 W	8600 lm	C	117,6 mm	F4,0 A	X		1
24061	400 W	8600 lm	C	117,6 mm	F4,0 A		X	1
10180	1000 W	20000 lm		189,1 mm	F6,3 A	X		1
10190	1500 W	30000 lm		254,0 mm	F*10,0 A	X		1
15700	2000 W	40000 lm		333,0 mm	F*10,0 A	X		1

10130	100 W	1450 lm	E	78,3 mm	F2,0 A	X		1
24130	100 W	1450 lm	E	78,3 mm	F2,0 A		X	1
10140	150 W	2000 lm	E	78,3 mm	F2,0 A	X		1
24140	150 W	2000 lm	E	78,3 mm	F2,0 A		X	1
10150	200 W	3000 lm	E	78,3 mm	F2,0 A	X		1
24150	200 W	3000 lm	E	78,3 mm	F2,0 A		X	1
15690	250 W	3800 lm	E	78,3 mm	F2,0 A	X		1
24690	250 W	3800 lm	E	78,3 mm	F2,0 A		X	1
15680	100 W	1000 lm	G	117,6 mm	F2,0 A	X		1
24680	100 W	1000 lm	G	117,6 mm	F2,0 A		X	1
15650	150 W	2000 lm	E	117,6 mm	F2,0 A	X		1
24650	150 W	2000 lm	E	117,6 mm	F2,0 A		X	1
10300	200 W	3000 lm	E	117,6 mm	F2,0 A	X		1
14520	250 W	3800 lm	E	117,6 mm	F2,0 A	X		1
10160	300 W	5000 lm	E	117,6 mm	F2,0 A	X		1
24160	300 W	5000 lm	E	117,6 mm	F2,0 A		X	1
10170	500 W	8500 lm		117,6 mm	F4,0 A	X		1
24170	500 W	8500 lm		117,6 mm	F4,0 A		X	1

Halogen-Hüllkolben / B15d Halogen with glass cover / B15d

Art.-Nr.	Bezeichnung	Socket	Leistung	Ausführung	Lichtstärke	VE
Art.-no.	Type	Socket	Wattage	Version	Lumin. Int.	Pack
10200	Hüllkolben	klar	150 W	E27	1850 lm	1
10202	Halogenstift	matt	75 W	B15d	900 lm	1
10201	Halogenstift	matt	100 W	B15d	1500 lm	1